

Molded plastic spray nozzles

SERIES







DIMENSIONS

| NOZZLE SIZE (BSPT) | Dim. D (mm) | Dim. H (mm) | Dim. L (mm) |
|-------------------------------|-------------------|-------------------|-------------------|
| 1/8 S | 16 | 14 | 21 |
| ¹ / ₄ S | 16 | 14 | 24 |
| ³/ ₈ S | 20 | 17 | 28 |
| 1/8SW | 16 | 14 | 16 |
| 1/8 SQ | 16 | 14 | 21 |
| ¹/₄SQ | 20 | 14 24 | |

FITTING SIZES:

1/8", 1/4" and 3/8" MALE BSPT (NPT also available)

STANDARD MODELS LISTED IN TABLES BELOW.

ADDITIONAL MODELS MAY BE AVAILABLE UPON REQUEST.

SPRAY CHARACTERISTICS:

These models produce a full cone spray pattern with spray angles of 60° to 120° @ 0.7 bar.

CONSTRUCTION:

Each BEX molded nozzle is designed with a series of "knobs" which makes them easier to finger tighten than a hex, especially when wet. The design feature of a small starter barrel greatly reduces the tendency to strip or crossthread the nozzle during installation.

MATERIALS AVAILABLE:

Polypropylene - excellent chemical and corrosion resistance. Useful up to 80°C.

Natural Polypropylene - non-pigmented for optimum purity.


PVDF - excellent durability and abrasion resistance and is inert to most chemicals. Many applications useful up to 150°C.

Natural PVDF where solution purity must be

SQ Model

optimized.





TYPICAL APPLICATIONS:

- Printed Circuit Board Washing
- PCB-Etching/Developing
- Semiconductor Manufacturing
- Carpet Cleaning
- Fruit and Vegetable Washing
- Plating Processes
- Dust Suppression
- Acid Spraying
- Degreasing
- Coating Applications
- Metal Washing
- Chemical Spraying
- Rinsing Parts

MOLDED PLASTIC S SERIES FULL CONE SPRAY MODELS (For capacity and spray angle data please refer to table on page 21)

| 1/8 Models | 1/8S1 | 1/8S1.5 | 1/8S3 | 1/8S3.5 | 1/8S5 | 1/8S6 |
|------------|---------|---------|--|---------|-------|-------|
| 1/4 Models | 1/4S6.5 | 1/4S7.5 | 1/4S10 | | | |
| 3/8 Models | 3/8S10 | 3/8S15 | SN4780 (70° spray angle/5.7 L/min @ 2.8 bar) | | | |

MOLDED PLASTIC SW WIDE ANGLE FULL CONE SPRAY MODELS (For capacity and spray angle data please refer to table on page 23)

| 1/8 Models | 1/8S2.8W | 1/8S4.3W | 1/8S5.6W | 1/8S8W |
|------------|----------|----------|----------|---------|
| 1/4 Models | 1/4S5.6W | 1/4S10W | 1/4S12W | 1/4S14W |

MOLDED PLASTIC SQ SERIES FULL CONE SPRAY MODELS (For capacity and spray angle data please refer to table on page 24)

| 1/8 Models | 1/8S4.8SQ | 1/8S5SQ | | | |
|------------|-----------|----------|----------|----------|--|
| 1/4 Models | 1/4S6SQ | 1/4S10SQ | 1/4S12SQ | 1/4S14SQ | |