

FULL CONE



SPRAY ANGLE	FLOW FACTOR	TIP COLOR	SPRAY TIPS AVAILABLE						CAPACITY LPM AT BAR							EQUIV. ORIFICE Ø (MM)
			Quick Change	Standard Ball	Threaded Tips NPT or BSPT				0.3 bar	0.7 bar	1 bar	1.5 bar	2 bar	3 bar	4 bar	
					1/8	1/4	3/8	1/2								
40°	16FC	Blue		•					3,99	5,65	6,92	7,98	9,78	11,30	13,84	2,49
	25FC	Red		•					6,25	8,83	10,81	12,50	15,29	17,66	21,61	3,18
45°	27FC	Pink		•					6,74	9,53	11,69	13,52	16,53	19,07	23,34	3,30
50°	50FC	Black		•					12,50	17,66	21,61	24,97	30,58	35,31	43,26	4,37
55°	30FC	Teal		•					7,49	10,59	13,00	14,97	18,36	21,19	25,95	3,58
60°	02FC	Dk Green	•			•	•	•	0,57	0,71	0,85	0,99	1,24	1,41	1,73	0,38
	03FC	Black	•	•		•	•	•	0,74	1,06	1,31	1,48	1,84	2,12	2,58	1,09
	04FC	Yellow			•				1,13	1,41	1,70	1,98	2,47	2,83	3,46	1,30
	05FC	Red	•		•	•	•	•	1,24	1,77	2,15	2,51	3,07	3,53	4,34	1,45
	07FC	Orange	•			•	•	•	1,73	2,47	3,11	3,53	4,41	5,12	6,32	1,91
	09FC	Lt Green	•			•	•	•	2,26	3,18	3,88	4,48	5,51	6,36	7,77	2,03
	10FC	Teal	•			•	•	•	2,51	3,53	4,31	4,98	6,11	7,06	8,48	2,06
	11FC	Yellow		•					2,75	3,88	4,77	5,51	6,71	7,77	9,50	2,11
	12FC	Pink	•	•		•	•	•	3,00	4,24	5,19	6,00	7,35	8,48	10,38	2,16
	15FC	Purple	•			•	•	•	3,74	5,30	6,50	7,49	9,18	10,59	12,96	2,39
	28FC	Red		•					6,99	9,89	12,11	13,98	17,13	19,78	24,22	3,35
	35FC	Blue		•					8,72	12,36	15,15	17,48	21,40	24,72	30,26	3,76
	40FC	Blue		•					9,89	14,13	17,30	20,13	24,37	28,25	34,61	3,96
65°	29FC	Dk Green		•					7,24	10,24	12,54	14,48	17,73	20,48	26,48	3,53
	52FC	Pink		•					13,00	18,36	22,49	25,95	31,78	36,73	44,95	4,52
80°	17FC	Yellow		•					4,24	6,00	7,84	8,48	10,24	12,36	14,69	2,59
90°	20FC	Blue					•		4,98	7,06	8,48	9,89	12,36	14,13	17,30	2,59
	25FC	Red					•		6,25	8,83	10,81	12,50	15,29	17,66	21,61	3,18
	30FC	Lt Green					•		7,49	10,59	13,00	14,97	18,36	21,19	25,95	3,58
	45FC	Black						•	11,30	15,89	19,42	22,60	27,54	31,78	38,84	4,11
	50FC	Purple						•	12,36	17,66	21,54	25,07	30,72	35,31	43,08	4,95
	53FC	Black		•					13,24	18,72	22,92	26,45	32,13	37,43	45,84	4,57
120°	20FC	Lt Blue					•		4,98	7,06	8,48	9,89	12,36	14,13	17,30	2,59
	25FC	Pink					•		6,25	8,83	10,81	12,50	15,29	17,66	21,61	3,18
	30FC	Dk Green					•		7,49	10,59	13,00	14,97	18,36	21,19	25,95	3,58
	45FC	Blue						•	11,30	15,89	19,42	22,60	27,54	31,78	38,84	4,11
	50FC	Lt Purple						•	12,36	17,66	21,54	25,07	30,72	35,31	43,08	4,95
	12053FC	Teal		•					13,24	18,72	22,92	26,45	32,13	37,43	45,84	4,57
									Custom Flow Rate and Spray Angle available upon request							

Custom Flow Rate and Spray Angle available upon request

HOLLOW CONE



30°	07HC	Teal	•						1,73	2,47	3,04	3,53	4,27	4,94	6,04	1,73
	11HC	Dk Green	•						2,75	3,88	4,77	5,51	6,71	7,77	9,50	2,11
	20HC	Red	•						4,98	7,06	8,65	9,99	12,22	14,13	17,30	2,77
	50HC	Grey	•						12,50	17,66	21,61	24,97	30,58	35,31	43,26	4,37
50°	08HC	Orange	•						2,01	2,83	3,46	3,99	4,91	5,65	6,92	1,83
	20HC	Orange	•						4,98	7,06	8,65	9,99	12,22	14,13	17,30	2,77
	29HC	Dk Green	•	•					7,24	10,24	12,54	14,48	17,73	20,48	26,48	3,53
	30HC	Blue		•					7,49	10,59	13,00	14,97	18,36	21,19	25,95	3,58
60°	15HC	Teal	•	•					3,74	5,30	6,50	7,49	9,18	10,59	12,96	2,39
65°	20HC	Orange		•					4,98	7,06	8,65	9,99	12,22	14,13	17,30	2,77
	25HC	Red		•					6,25	8,83	10,81	12,50	15,29	17,66	21,61	3,18
	28HC	Blue		•					6,99	9,89	12,11	13,98	17,13	19,78	24,22	3,35
	35HC	Blue		•					8,72	12,36	15,15	17,48	21,40	24,72	30,26	3,76
	50HC	Black	•	•					12,50	17,66	21,61	24,97	30,58	35,31	43,26	4,37
90°	08HC	Blue		•					2,01	2,83	3,46	3,99	4,91	5,65	6,92	1,83

Custom Flow Rate and Spray Angle available upon request



Deflector in QC TIP



QC - Hollow Cone have Deflector in Adapter BALL

PROUDLY SERVING THE FOLLOWING INDUSTRIES



FOOD & BEVERAGE



LANDSCAPING



APPLIANCES



AGRICULTURE



HVAC



WATER PARKS



MARINE



LIQUID FUELS



INDUSTRIAL



AUTOMOTIVE



MEDICAL



LABORATORIES



LIGHTING



CONSTRUCTION