

## QUIK-RELEASE NOZZLE ASSEMBLIES

- Uni-Spray Nozzles are injection molded from custom-blended polypropylene, a cost-effective material that is corrosion and heat-resistant and impervious to most chemicals.
- The tip design resists clogging and buildup due to its smooth shape and low coefficient of friction.
- A wide variety of Uni-Spray Clamp-On Nozzles are available to suit your application and are colour-coded for easy identification (see table below).
- All nozzles are available with a Single-Spring (pressures between 0 to 4.0 bar or an optional Double-Spring configuration (pressures between 4.0 bar to 10.0 bar)
- All nozzles are available in three spigot sizes, to fit 14 mm, 17 mm and 19 mm diameter holes in the riser.

## Mark 1 Adjustable Nozzle Assembly

- Permits directional adjustment of the nozzle tip anywhere within a 45° included angle.
- Interchangeable Nozzle Tips are available in Full Cone, Hollow Cone or Flat Spray styles with various combinations of spray angle and flow rate.
- The Mark 1 is also available with a Threaded Ball Connection in 1/8", 1/4", 3/8" and 1/2" BSP, allowing the use of any threaded plastic, brass or steel nozzle.
- Refer to pages 4 and 5 for Assembly Details and Ordering Information, pages 14 and 15 for Tip Selection and page 13 for Replacement Parts.

## Mark 2 Fixed Nozzle Adapter

- Offers female threaded connections in 1/8", 1/4", 3/8" and 1/2" BSP threads, allowing the use of any threaded plastic, brass or steel nozzle.
- See pages 6 and 7 for Assembly Details and Ordering Information.

## Available Sizes

The Mark 1 and Mark 2 Nozzle Assemblies are colour-coded for convenient identification, and are available to fit the following pipe sizes:

Pipe size	Reg. Spigot 17 mm	Sm. Spigot 14 mm	Lg. Spigot 19 mm	Spigot Size 10 mm
3/4"	—	—	—	Black
1"	Blue	Lt Blue	Lt Blue	-
1-1/4"	Red	Pink	Pink	—
1-1/2"	Purple	Mauve	Mauve	_
2"	Green	Lime Green	Lime Green	_



